

SAFETY DATA SHEET

SECTION 1 - Identification of the Product and Company

1.1 Product Name Kim-Kut Grinding Wheel 87-114, 87-115, 87-131, 87-134, 87-136

1.2 Product Use For material removal. See ANSI B7.1-2000

1.3 Company Details: Kimball Midwest

Address: 4800 Roberts Road

Columbus, OH 43228

Phone: 800-233-1294

Emergency Phone: 800-424-9300 (Chemtrec)

SECTION 2 - Hazard Information

2.1 Precautionary statements

Wear Respirator, eye protection, and protective clothing when using product

Product will produce sparks and debris when in use, avoid using product near reactive or flammable

substances or electrical equipment

Discard if product comes in contact with water

2.2 Description of Hazards

Respiratory Wheel dust is a respiratory irritant

Skin Wheel dust and fiberglass reinforcement is a skin irritant

Ingestion Acute product toxicity unknown

Eyes Wheel Dust is an eye irritant

Chronic Potential Chronic Effects include skin sensitization and restricted breathing

Hazard Status This product is classified as non hazardous under OSHA HCS 29 CFR 1910.1200

SECTION 3 - Composition

<u>Ingredient</u>	<u>Formula</u>	% Weight	Cas #
Aluminum Oxide	Al_2O_3	60 - 80	1344-28-1
Silicon Carbide	SiC	0-70	409-21-2
Zirconium Oxide	ZrO ₂	0 - 12	1314-23-4
Calcium Hydroxide	Ca(OH) ₂	0-1	1305-62-0
Barium Sulfate	BaSO ₄	0-10	7727-43-7
Iron Sulfide	FeS ₂	0-18	12068-85-8
Alkali Aluminum Fluorides	-	0-15	15096-52-3/ 60304-36-1
Cured Phenolic Resin	-	0 - 15	N/A
Glass Fiber	-	0 - 5	N/A
Steel	-	0.1 - 1	N/A
Carbon Black	-	trace	N/A
Zinc	Zn	N/A	N/A

SECTION 4-First Aid

4.1 First Aid for exposure

Dust Inhalation: Terminate exposure and remove to fresh air. Obtain medical assistance.

Ingestion: Obtain medical assistance.

Absorption: N/A

Skin contact: Terminate exposure and remove to fresh air. Obtain medical assistance.

Eye: Flush eyes with water.

4.2 Signs and Symptoms of Exposure

Acute: May cause coughing and shortness of breath during grinding.

Skin irritation. Eye irritation.

SECTION 5 - Fire Fighting Measures

5.1 Flammable Properties: None

Means Of Extinction: Water or carbon dioxide

Special Fire Fighting Procedures: Consult NFPA or CFPA procedures

Unusual Fire or Explosion Hazards: None

SECTION 6 - Accidental Release Measures

Normal clean up procedures should be used if material is released

Use of gloves to clean up spent wheels is recommended

SECTION 7- Storage, Handling and Use Procedures

Handling: Avoid damage to wheel. Do not drop.

Always handle in accordance with ANSI B7.1.

Use: Always use in accordance with ANSI Z43.1 and OSHA 1910.215. Do not use

dropped or damaged wheels. Do not use without machine guard in place.

Do not exceed maximum RPM on wheel.

Storage: Avoid excessive temperatures in storage. Store in a dry area.

SECTION 8- Personal Protective Control Measures

8.1 Control Measures

Protection: Requirements and Referrals.

Respiratory: OSHA/NIOSH approved respirator. See OSHA 29 CFR 1910.134 or European Standard EN 149.

Ventilation: Engineering Controls recommended. See ANSI Z43.1. Refer to OSHA 29 CFR 1910.94.

Protective Gloves: Leather gloves.

Eye Protection: Protective eyewear such as safety glasses or face shield. Refer to OSHA 29 CFR 1910.133.

Hearing Protection: Hearing protection such as approved ear muffs or ear plugs. Refer to OSHA 29 CFR 1910.95.

Body Protection: Leather apron, chaps, or shoe coverings to shield from heavy spark showers in operation.

Hygienic Practices: Wash with soap and water after handling and grinding.

8.2 Exposure

Chemical OSHA PEL **ACGIH TLV** Aluminum C NA 10mg/m³ Silicon Carb NA 10mg/m3 Zirconium C NA 10mg/m³ Calcium Hy NA 5mg/m³ Barium 5mg/m³ 10mg/m³ Iron Dis NA 10mg/m

Alkali Aluminum Fluorides 2.5mg/m³ 2.5mg/m³ (As F)

Phenolic ReN/AN/AFiber Gl 5mg/m^3 10mg/m^3 Carbon 3.5 mg/m^3 3.5 mg/m^3

SECTION 9- Physical/Chemical Characteristics

Boiling Point	N/A	(H20=1 Specific Gravity	2 - 4
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (AIR=1)	N/A	Evaporation Rate (Butyl Acetat	te=1) N/A
Solubility in Water	Insoluble	Appearance	Dark colored solid
Lower And Upper Explosion Limits	N/A	Odor	burning plastic odor in use
Flammable Limits	N/A	Degradation Temperature	~ 800 F (427 C)
Flash Point	N/A		

SECTION 10 - Stability and Reactivity Data

Stable - Avoid excessive moisture and humidity, temperature extremes and contact with acids or solvents

Not incompatible with any materials

Hazardous Polymerization will not occur

Dust and organic fumes are generated in use

SECTION 11 - Toxicological Data

11.1 Acute Toxicological Effects

Chemical	Route of Exposure	Acute LD50
Aluminum Oxide	oral	>5000 mg/kg (rat)
Zirconium Oxide	oral	>8800 mg/kg (mouse)
Glass fiber	N/A	N/A
Alkali Aluminum Fluorides	oral	>5000 mg/kg (rat)
Cured Phenolic resin	N/A	N/A
Carbon black	oral	8000 mg/kg (rat)
Silicon Carbide	N/A	N/A
Calcium Hydroxide	oral	7340 mg/kg (rat)
Barium Sulfate	N/A	N/A
Iron Disulfide	N/A	N/A

11.2 Toxological Effects

Dust Inhalation Coughing and shortness of breath, aggravation, decreased lung capacity

of medical conditions such as asthma or emphysema

Ingestion Can cause stomach pain, vomiting and diarrea

Absorption N/A

Skin contact Grinding wheel may cause abrasions

Dust may cause skin irritation

Eye Dust or fumes may cause eye irritation

Carcinogenicity Unknown
Mutagenicity Unknown
Reproductive Effects Unknown

Section 12-Ecological Information

No Data Available

Section 13-Disposal Considerations

Dispose in accordance to local and federal regulations

Section 14-Transport Information

Not regulated as a hazardous material for transport

Section 15-Regulatory Information

No Data Available

Section 16-Other Information

SDS Revision Date: November 1, 2014
Reason for Update: Mandated Update

Preparation By: Supplier

COMPANY USE

The information and recommendations set forth herein are taken from sources and references believed to be accurate and complete as of the date hereof. However, Kimball Midwest makes no expressed or implied warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.