

# SEIZE RELEASE COPPER

## Anti-Seize Compound Safety Data Sheet

### SECTION 1: IDENTIFICATION

**Kimball Midwest part #:** 80-307

**Product Name: Manufacturer / Supplier:** Kimball Midwest  
4800 Roberts Road  
Columbus, Oh 43228

**Phone:** 800-233-1294

**Web:** kimballmidwest.com

**Emergency Phone Number:** Chemtrec 1-800-424-9300

**Restriction on Use:** None known

**SDS Date of Preparation:** June 18, 2021

### SECTION 2: HAZARDS IDENTIFICATION

**GHS Classification (Hazcom 2012):**

Flammable Aerosol Category 1

Gases Under Pressure – Compressed Gas

Skin Irritation Category 2

Eye Irritation Category 2A

Aspiration Hazard Category 1

Specific Target Organ Toxicity – Single Exposure Category 3 (Narcotic effects)

**Label Elements:**



**Signal Word :** DANGER

**Hazard Phrases:**

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
Causes skin irritation.  
Causes serious eye irritation.  
May be fatal if swallowed and enters airways.  
May cause drowsiness or dizziness.

**Precautionary Phrases:****Prevention:**

Wash thoroughly after handling.  
Wear protective gloves, eye and face protection.  
Avoid breathing mist or spray.  
Use only outdoors or in a well-ventilated area.  
Take off contaminated clothing and wash it before reuse.  
Keep away from heat, sparks, open flames or hot surfaces. No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

**Response**

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**IF ON SKIN:** Wash with plenty of water. If skin irritation occurs: Get medical attention.

**IF SWALLOWED:** Immediately call a POISON CENTER or doctor.

Do NOT induce vomiting.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor if you feel unwell.

**Storage**

Store in a well-ventilated place.  
Store locked up.  
Store at temperatures not exceeding 120°F

**Disposal**

Dispose of contents in accordance with local, regional and national regulations.

**Other Hazards:** None

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

| Chemical Name   | CAS#       | %     |
|---|------------|-------|
| Acetone   | 67-64-1    | 20-30 |
| Heptane   | 142-82-5   | 15-25 |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | 64742-65-0 | 8-12  |
| Distillates (petroleum), hydrotreated heavy naphthenic    | 64742-52-5 | 8-12  |
| Propane   | 74-98-6    | 5-15  |

|          |           |      |
|----------|-----------|------|
| Butane   | 106-97-8  | 5-15 |
| Copper   | 7440-50-8 | 5-8  |
| Graphite | 7782-42-5 | 3-7  |

**The specific identity and/or exact percentage of composition has been withheld as a trade secret.**

|                                      |
|--------------------------------------|
| <b>SECTION 4: FIRST AID MEASURES</b> |
|--------------------------------------|

**Eye:** Immediately flush eyes with water, holding the eyelids apart. Get medical attention if irritation develops or persists.

**Skin:** In case of contact, wash thoroughly with plenty of water. Get medical attention if irritation persists.

**Inhalation:** Remove to fresh air and keep comfortable for breathing. If irritation occurs, get medical attention.

**Ingestion:** Aspiration Hazard. DO NOT induce vomiting. Get immediate medical attention.

**Most Important symptoms and effects, both acute and delayed:** Causes eye and skin irritation. Product is an aspiration hazard. May enter the lungs during swallowing or vomiting and cause lung damage. Inhalation may cause irritation, headache, dizziness and drowsiness.

**Indication of any immediate medical attention and special treatment needed:** Immediate medical attention required for ingestion.

|  |
|--|
| <b>SECTION 5: FIRE-FIGHTING MEASURES</b> |
|--|

**Suitable and Unsuitable Extinguishing Media:** Use water spray or fog, foam, carbon dioxide or dry chemical.

**Special Hazards Arising from the Chemical:** Extremely flammable aerosol. Keep away from heat and open flames. Container may rupture or explode in the heat of a fire. Prolonged exposure to temperatures above 120°F may cause cans to burst. Combustion may produce carbon dioxide, carbon monoxide.

**Special Equipment and Precautions for Fire-Fighters:** Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water. Protect against bursting cans.

|   |
|---|
| <b>SECTION 6: ACCIDENTAL RELEASE MEASURES</b> |
|---|

**Personal Precautions, Protective Equipment and Emergency Procedures:** Wear appropriate personal protective equipment. Eliminate all sources of ignition with explosion-proof equipment. Ventilate area.

**Environmental Hazards:** Report spills and releases as required to appropriate authorities.

**Methods and Material for Containment and Cleaning Up:** Place leaking container into a suitable container and place in a well-ventilated area until the propellant has dissipated. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal.

**SECTION 7: HANDLING AND STORAGE**

**Precautions for Safe Handling:** Avoid contact with eyes. Avoid breathing vapors and mists. Use with adequate ventilation. Keep away from heat sources. Contents under pressure. Do not puncture or incinerate container. Do not smoke while using.

**Conditions for Safe Storage, Including any Incompatibilities:** Store in a cool, well-ventilated area at temperatures below 120°F. Do not store in direct sunlight.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

| Chemical Name   | Exposure Limits  |
|---|--|
| Acetone   | 500 ppm TWA ACGIH TLV<br>750 ppm STEL ACGIH TLV<br>1000 ppm TWA OSHA PEL   |
| Heptane   | 400 ppm TWA ACGIH TLV<br>500 ppm STEL ACGIH TLV<br>500 ppm TWA OSHA PEL  |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | 5 mg/m <sup>3</sup> TWA ACGIH TLV (inhalation)   |
| Distillates (petroleum), hydrotreated heavy naphthenic    | None Established   |
| Propane   | 1000 ppm TWA OSHA PEL  |
| Butane  | 1000 ppm STEL ACGIH TLV  |
| Copper, dust or fume                                      | 1 mg/m <sup>3</sup> TWA ACGIH TLV<br>1 mg/m <sup>3</sup> TWA OSHA PEL  |
| Graphite  | 2 mg/m <sup>3</sup> TWA ACGIH TLV respirable<br>15 mg/m <sup>3</sup> TWA OSHA PEL total dust<br>5 mg/m <sup>3</sup> TWA OSHA PEL respirable fraction |

**Appropriate Engineering Controls:** Use with adequate general or local exhaust ventilation to maintain exposure levels below the exposure limits .

**Individual Protection Measures:**

**Respiratory Protection:** In operations where the occupational exposure limits are exceeded, a NIOSH approved respirator with organic vapor/particulate cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

**Skin Protection:** Impervious gloves such as nitrile recommended where needed to avoid prolonged skin contact .

**Eye Protection:** Safety goggles recommended where needed to avoid eye contact.

|  |
|--|
| <b>SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES</b> |
|--|

|  |   |
|--|---|
| <b>Appearance:</b> Aerosol   | <b>Vapor Density (air = 1):</b> >1                                  |
| <b>Odor:</b> Mild odor   | <b>Specific Gravity:</b> 0.7  |
| <b>Odor Threshold:</b> Not established   | <b>Water Solubility:</b> Not soluble                                |
| <b>pH:</b> Not available   | <b>Octanol/Water Partition Coefficient:</b> Not available           |
| <b>Melting Point/Freezing Point:</b> Not available                                     | <b>Autoignition Temperature:</b> Not available                      |
| <b>Boiling Point:</b> -44 to 208 °F  | <b>Decomposition Temperature:</b> Not available                     |
| <b>Flash Point:</b> -141 °F (propellant)   | <b>Viscosity:</b> Not available                                     |
| <b>Evaporation Rate:</b> Not available   | <b>Explosion Properties:</b> None                                   |
| <b>Flammable Limits:</b><br><b>LEL:</b> Not established<br><b>UEL:</b> Not established | <b>Oxidizing Properties:</b> Not oxidizing                          |
| <b>Vapor Pressure:</b> Not established   | <b>Aerosol Fire Protection Level:</b> Level 2<br>Aerosol (NFPA 30B) |
| <b>VOC Content:</b> 39.81%   | <b>Flammability (solid, gas):</b> Propellant is a flammable gas     |

|   |
|---|
| <b>SECTION 10: STABILITY AND REACTIVITY</b> |
|---|

**Reactivity:** Not reactive under normal conditions of use.

**Chemical Stability:** Stable under normal storage and handling conditions.

**Possibility of Hazardous Reactions:** None known.

**Conditions to Avoid:** Keep away from heat, sparks, flames and other sources of ignition. Dropping containers may cause bursting.

**Incompatible Materials:** Avoid strong oxidizing agents and acids. Concentrated oxygen.

**Hazardous Decomposition Products:** Thermal decomposition may produce carbon dioxide, carbon monoxide.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Potential Health Effects:

**Eye:** Causes serious eye irritation.

**Skin:** Contact may cause irritation and drying of the skin.

**Inhalation:** Mist or vapor can irritate the throat and lungs. High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

**Ingestion:** If swallowed, this material may cause irritation of the mouth, throat and esophagus. Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness and other central nervous system effects. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

**Chronic Hazards:** None known.

**Carcinogen Status:** None of the components of this product are listed as carcinogens by IARC, NTP or OSHA.

**Acute Toxicity Values:** Acetone: Oral rat LD50: 5800 mg/kg, dermal rabbit LD50 >7426 mg/kg available.

**Heptane:** Oral rat LD50 >5000 mg/kg, inhalation rat LC50  $\geq$  29.29 mg/L, dermal rabbit LD50 >2000 mg/kg

**Distillates (petroleum), solvent-dewaxed heavy paraffinic:** Oral rat LD50 > 5000 mg/kg

Inhalation rat LC50: 2.18 mg/L, Dermal rabbit LD50 > 2000 mg/kg

**Distillates (petroleum), hydrotreated heavy naphthenic:** Oral rat LD50 > 5000 mg/kg, Inhalation rat LC50: 1.8 mg/L, dermal rabbit LD50 > 2000 mg/kg

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity:

**Acetone:** Acute: *Ulva pertusa* EC50: 20.565 mg/L/96h, *Gammarus pulex*: 6000 mg/L/48hr, *Daphnia magna*: 10 mg/L/48hr, *Pimephales promelas* Juvenile: 100 mg/L/96hr

**Chronic:** *Ulva pertusa* NOEC: 4.95 mg/L/96hr, *Daphniidae* NOEC: 0.016 ml/L/21days, *Daphnia magna* NOEC: 0.1 ml/L/21days

**Persistence and Degradability:** Acetone and heptane are readily biodegradable.

**Bioaccumulative Potential:** Acetone is not Bioaccumulative. Heptane may bioaccumulate based on a log Kow of 4.66

**Mobility in Soil:** No data available

**Other Adverse Effects:** None known

### SECTION 13: DISPOSAL CONSIDERATIONS

Dispose in accordance with all local, regional and national regulations. Do not puncture or incinerate containers. When contents are depleted, continue to depress button until all gas is expelled.

### SECTION 14: TRANSPORT INFORMATION

**DOT Proper Shipping Name:** UN1950, Aerosols, 2.1, Limited Quantity

**DOT Technical Name:** None

**DOT Hazard Class:** 2.1

**UN Number:** UN1950

**DOT Labels Required (49CFR172.101):** LTD QTY

**IMDG Shipping Description:** UN1950, Aerosols, 2.1, FP -17 C, Limited Quantity, Marine Pollutant

**ID Number:** UN1950

**Hazard Class:** 2.1

**Packing Group:** None

**Labels Required:** None

**Marking Required:** Limited Quantity Mark

**Placards Required:** Limited Quantity and Marine Pollutant Mark On Transport Containers

#### ICAO/IATA

**Proper shipping name:** Aerosol, Flammable

**Hazard Class:** 2.1

**Identification Number:** UN 1950

**Packing Group:** None

### SECTION 15: REGULATORY INFORMATION

**Safety, health, and environmental regulations specific for the product in question.**

**CERCLA Hazardous Substances (Section 103)/RQ:** This product has an RQ of 16,666 lbs based on the RQ for acetone of 5000 lbs. In addition, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**SARA Hazard Category (311/312):** Fire Hazard, Pressure Hazard, Acute Health

**SARA 313:** This product contains the following chemicals regulated under SARA Title III, section 313: None

**EPA TSCA Inventory:** All of the components of this product are listed on the TSCA inventory.

**CALIFORNIA PROPOSITION 65:** This product is not known to contain listed chemicals.

## SECTION 16: OTHER INFORMATION

**Revision Summary:** New format to comply with OSHA Hazcom 2012

---

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.