Date of issue: 03/12/2025 Revised On 03/12/2025

1 Identification of the substance and manufacturer

Trade name: **BB BROWN**

Other means of identification

KB00080329 Product code:

Article category

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use. Kimball Midwest Manufacturer/Supplier:

4800 Roberts Road Columbus, OH 43228 800-233-1294

www.kimballmidwest.com ChemTrec: 800-424-9300 **Emergency telephone number:**

2 Hazard(s) identification

Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

Eye irritation 2A H319 Causes serious eye irritation.

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

H336 Specific target organ toxicity (single exposure) 3 May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: GHS Hazard pictograms

Precautionary statements







GHS02 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes serious eye irritation.

Suspected of causing cancer. Route of exposure: Inhalation.

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. Avoid breathing fume/mist/vapors/spray. Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.
Get medical advice/attention if you feel unwell. If eye irritation persists: Get medical advice/attention.

Store in a well ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

		The production of the constant			
Dangerou	s components:				
67-64-1	Acetone		25-50%		
78-93-3	methyl ethyl ketone		10-15%		
	propane		10-15%		
108-10-1	methyl isobutyl ketone		≥5-<10%		
106-97-8	n-butane		5-10%		
	PM acetate		1-5%		
2807-30-9	Glycol Ether EP		1-5%		

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After eye contact: After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects: Dizziness

(Contd. on page 2)

(Contd. of page 1)

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: BB BROWN

Indication of any immediate medical

No further relevant information available. attention needed:

5 Fire-fighting measures

Extinguishing agents: Special hazards:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

Protective equipment for firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values t	hat require monitoring at the workplace:
07 04 4 4	

01	-0	4 - I	A		OHE
PF	=	(U	SA)	Lon

Long-term value: 2400 mg/m³, 1000 ppm REL (USA) Long-term value: 590 mg/m³, 250 ppm TLV (USA) Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm

A4, BEI

78-93-3 methyl ethyl ketone

PEL (USA) Long-term value: 590 mg/m³, 200 ppm Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm REL (USA)

Short-term value: 150 ppm TLV (USA)

Long-term value: 75 ppm BEI, Skin

74-98-6 propane

Long-term value: 1800 mg/m³, 1000 ppm PEL (USA) REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) see Appendix F Minimal oxygen content (D, EX)

108-10-1 methyl isobutyl ketone

PEL (USA) Long-term value: 410 mg/m³, 100 ppm REL (USA)

Short-term value: 300 mg/m³, 75 ppm Long-term value: 205 mg/m³, 50 ppm

Short-term value: 307 mg/m³, 75 ppm TLV (USA) Long-term value: 82 mg/m³, 20 ppm

BEI, A3

106-97-8 n-butane

Long-term value: 1900 mg/m³, 800 ppm REL (USA) TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

(EX) 108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

78-93-3 methyl ethyl ketone

BEI (USA) 2 mg/L

Medium: urine

Time: end of shift

Parameter: Methyl ethyl ketone (nonspecific)

(Contd. on page 3)

(Contd. of page 2)

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: BB BROWN

108-10-1 methyl isobutyl ketone

BEI (USA) 1 mg/L Medium: urine

Hand protection:

Time: end of shift Parameter: MIBK

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Physical state Aerosol Odor: Aromatic Odor threshold: Not determined. Melting point/Melting range Undetermined. Boiling point: -44.5 °C (-48.1 °F) Extremely flammable. Flammability:

Lower Explosion Limit: 1.7 Vol % 11.5 Vol % -19 °C (-2.2 °F) Upper Explosion Limit: Flash point: Extremely flammable. Flammability (solid, gas): Decomposition temperature: Not determined. pH-value: Not determined. Viscosity: Not determined. Solubility: Not determined. Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. Particle characteristics Not applicable. Appearance: Aerosol.

Ignition temperature: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Water: 0.0 %

Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

	_				
LD/LC50 v	LD/LC50 values that are relevant for classification:				
78-93-3 m	78-93-3 methyl ethyl ketone				
Oral	LD50	3,300 mg/kg (rat)			
Dermal	LD50	5,000 mg/kg (rbt)			
108-10-1 ו	1 methyl isobutyl ketone				
Oral	LD50	2,100 mg/kg (rat)			
Dermal	LD50	16,000 mg/kg (rab)			
Inhalative	LC50/4 h	11 mg/l (ATE)			
		8.3-16.6 mg/l (rat)			
108-65-6 I	108-65-6 PM acetate				
Oral	LD50	8,500 mg/kg (rat)			
Inhalativa	1 C50/4 h 35 7 mg/l (rat)				

Inhalative LC50/4 h 35.7 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

(Contd. on page 4)

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: BB BROWN

Sensitization: No sensitizing effects known. (Contd. of page 3)

12 Ecological information

Aquatic toxicity:

Hazardous for water, do not empty into drains.

Persistence and degradability:

The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.

Bioaccumulative potential: Mobility in soil:

No further relevant information available. No further relevant information available. No further relevant information available.

13 Disposal considerations

Other adverse effects:

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

Water, if necessary with cleansing agents. Recommended cleansing agent:

14 Transport information

UN-Number UN1950 DOT UN1950

DOT Aerosols, flammable 1950 AEROSOLS **ADR**

Transport hazard class(es):

Class Special marking (IATA): 2.1 Gases

Packaging Group:

Warning: Gases Special precautions for user:

EMS Number: F-D,S-Ŭ

UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-10-1 methyl isobutyl ketone

Toxic Substances Control Act

(TSCA):

Canadian Domestic Substances List

(DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

All ingredients are listed or exempted.

California Proposition 65 chemicals known to cause cancer:

108-10-1 methyl isobutyl ketone

13463-67-7 titanium dioxide

1333-86-4 Carbon black

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

EPA:

67-64-1 Acetone

78-93-3 methyl ethyl ketone ı ı

All ingredients are found on the inventory list of substances.

108-10-1 methyl isobutyl ketone

16 Other information

Contact: Regulatory Affairs