(Contd. on page 2)

1 Identification of the substance a	and manufacturer
Trade name:	DD GREEN
Product code:	80-907
Recommended use:	Paint and coatings application.
Uses advised against:	Any that differs from the recommended use.
Manufacturer/Supplier:	Kimball Midwest
	4800 Roberts Road Columbus, OH 43228
	800-233-1294
Employee to be a base of the second second second	www.kimballmidwest.com
Emergency telephone number:	ChemTrec: 800-424-9300
2 Hazard(s) identification	
Classification of the substance or n	nixture
Flammable Aerosols 1	H222 Extremely flammable aerosol.
Gases under Pressure - Liquefied gas	
Eye Irritation 2A	H319 Causes serious eye irritation.
Carcinogenicity 2	H351 Suspected of causing cancer. Route of exposure: Inhalation.
Specific Target Organ Toxicity - Single	
Specific Target Organ Toxicity - Repe	ated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.
Additional information: GHS Hazard pictograms	\land \land \land \land
ono nazara pietograma	$\langle \psi \rangle \langle - \rangle \langle 1 \rangle \langle 4 \rangle$
	$\forall \lor \lor \lor$
	GHS02 GHS04 GHS07 GHS08
Signal word	Danger
Hazard statements	Extremely flammable aerosol. Contains gas under pressure; may explode if heated.
	Causes serious eve irritation.
	Suspected of causing cancer. Route of exposure: Inhalation.
	May cause drowsiness or dizziness.
Precautionary statements	May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use.
r roodutional y otatomonto	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	Do not spray on an open flame or other ignition source.
	Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.
	Wash thoroughly after handling.
	Use only outdoors or in a well-ventilated area.
	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and
	easy to do. Continue rinsing.
	Call a poison center/doctor if you feel unwell.
	If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place.
	Store locked up.
	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
	Dispose of contents/container in accordance with local/regional/national/international regulations.
3 Composition/information on ing	redients

5 Composi	o composition/mormation on ingredients		
	Chemical characterization: Mixtures Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.		
Dangerous	components:		
67-64-1	Acetone		25-50%
	propane		15-25%
110-19-0	Isobutyl Acetate		10-15%
106-97-8	n-butane		5-10%
	butyl acetate		5-10%
13463-67-7	titanium dioxide		1-5%
2807-30-9	Glycol Ether EP		1-5%

4 First-aid measures	
After inhalation: After skin contact: After eye contact: After swallowing:	Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects:	Dizziness

Printing date 06/10/2022

Safety Data Sheet

Revised On 06/10/2022

Indication of any imm attention needed:	ediate medica	Contd. of page No further relevant information available.
5 Fire-fighting measu	res	
Extinguishing agents: Special hazards: Protective equipment for firefighters:		CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.
		A respiratory protective device may be necessary.
6 Accidental release r	neasures	
Personal precautions	protective	
equipment and emerg procedures:	ency	Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material	for	Use respiratory protective device against the effects of futnes/dust/acrosol.
containment and clea	ning up:	Absorb liquid components with liquid-binding material.
7 Handling and storage	ae	
Precautions for safe h Storage requirements	andling	Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditior Store locked up.
8 Exposure controls/	personal prot	ection
	•	equire monitoring at the workplace:
67-64-1 Acetone		
PEL (USA) Long-term		
REL (USA) Long-term		
TLV (USA) Short-term	value: 500 ppm	1
A4. BEI	value: 250 ppm	
,		
74-98-6 propane	value, 1000 m a	
PEL (USA) Long-term		
REL (USA) Long-term		
TLV (USA) see Appen		
110-19-0 Isobutyl Ace		
PEL (USA) Long-term		
REL (USA) Long-term		
TLV (USA) Short-term	value: 150 ppm value: 50 ppm	
106-97-8 n-butane	value. 30 ppm	
REL (USA) Long-term	value: 1000 mg	/m ³ 800 nnm
TLV (USA) Short-term		
(EX)	value. 1000 pp	111
123-86-4 butyl acetate	1	
PEL (USA) Long-term		m ³ , 150 ppm
REL (USA) Short-term		
Long-term	value: 710 mg/ı	m³, 150 ppm
TLV (USA) Short-term	value: 150 ppm)
Long-term	value: 50 ppm	
Ingredients with biolo	gical limit valu	Ies:
67-64-1 Acetone		
BEI (USA) 25 mg/L		
Medium: ur		
Time: end c	Acetone (nonsp	
Hygienic protection:		Immediately remove all soiled and contaminated clothing.
riygienic protection.		Wash hands after use. Avoid contact with the eyes and skin.
		Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas.
Due ettel		A resourator is denerally not necessary when lising this product olifdoors or in large open areas
Breathing equipment:		cases where short and/or long term overexposure exists, a charcoal filter respirator should be wo If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.
Breathing equipment: Hand protection:		cases where short and/or long term overexposure exists, a charcoal filter respirator should be wo

Page 2/4

Printing date 06/10/2022

Safety Data Sheet

Revised On 06/10/2022

(Contd. of page 2)

Eye protection:	Tightly sealed goggles	(Contd. of page 2)
9 Physical and chemical properties		
Appearance:	Aerosol.	
Odor: Odor threshold:	Aromatic Not determined.	
pH-value: Melting point/Melting range Boiling point:	Not determined. Undetermined. -44 °C (-47.2 °F)	
Flash point: Flammability (solid, gas):	-19 °C (-2.2 °F) Extremely flammable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not self-igniting.	
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol %	
Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octonal/water		
Solubility: Viscosity: Water:	Not determined. Not determined. 0.0 %	
10 Stability and reactivity		
Reactivity: Conditions to avoid:	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do no temperatures.	ot warehouse in subfreezing
Chemical stability: Possibility of hazardous reactions: Incompatible materials: Hazardous decomposition:	Not fully evaluated. No dangerous reactions known. No further relevant information available. No dangerous decomposition products known.	
11 Toxicological information		
LD/LC50 values that are relevant for	classification:	
110-19-0 Isobutyl Acetate		
Oral LD50 4,763 mg/kg (rbt)		
123-86-4 butyl acetate	N	
Oral LD50 14,000 mg/kg (rat)	
Inhalative LC50/4 h >21 mg/l (rat)		
13463-67-7 titanium dioxide Oral LD50 >20.000 mg/kg (rational stress)	st)	
Oral LD50 >20,000 mg/kg (ra Dermal LD50 >10,000 mg/kg (rt		
Inhalative LC50/4 h >6.82 mg/l (rat)		
Information on toxicological effects:	No data available.	
Skin effects:	No irritant effect.	
Eye effects:	Irritating effect.	
Sensitization:	No sensitizing effects known.	
12 Ecological information		
Aquatic toxicity:	Hazardous for water, do not empty into drains.	
Persistence and degradability: Other information:	The product is degradable after prolonged exposure to natural weath This product does not contain any chlorofluorocarbons (CFC' (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, le	s), hydrochlorofluorocarbons
Bioaccumulative potential: Mobility in soil: Other adverse effects:	solvents. No further relevant information available. No further relevant information available. No further relevant information available.	
13 Disposal considerations		
Dispose of in accordance with local, st	ate, and federal regulations. Do not puncture, incinerate, or compac cut empty containers with electric or gas torches.	t. Partially empty cans must be
Recommendation:	Completely empty cans should be recycled.	(Contd. on page 4)

Trade name: ALPINE GREEN

Page 4/4

Revised On 06/10/2022

Recommended cleansing agent:	Water, if necessary with cleansing agents. (Contd. of page
4 Transport information	
UN-Number	UN1950
DOT	UN1950
DOT	DOT
	Aerosols, flammable
ADR	1950 Aerosols
Transport hazard class(es): Class	2.1 Gases
Marine pollutant:	No
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-Ŭ
Packaging Group:	
UN "Model Regulation":	UN1950, Aerosols, 2.1
5 Regulatory information SARA Section 355 (extremely haza	Indous substances):
None of the ingredients in this produc	
SARA Section 313 (Specific toxic of	
None of the ingredients is listed.	
Toxic Substances Control Act	
(TSCA):	All hazardous ingredients are found on the inventory list of substances.
Canadian Domestic Substances Li	
(DSL):	All ingredients are listed or exempted.
Consumer Product Safety	
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.
California Proposition 65 chemica	Is known to cause cancer:
13463-67-7 titanium dioxide	
108-10-1 methyl isobutyl ketone	
100-41-4 ethyl benzene	
1333-86-4 Carbon black	
Prop 65 chemicals known to cause	e birth defects or reproductive harm:
108-10-1 methyl isobutyl ketone	·
EPA:	
67-64-1 Acetone	
110-19-0 Isobutyl Acetate	']
110-19-0 ISODULYI Acetale	
6 Other information	
Contact:	Regulatory Affairs