

Safety Data Sheet

Date of issue: 07/17/2025

Revised On 03/12/2025

1 Identification of the substance and manufacturer

Trade name: GLOSS DOVE LIGHT GRAY
 Other means of identification
 Product code: 80-918
 Article category
 Recommended use: Paint and coatings application.
 Uses advised against: Any that differs from the recommended use.
 Manufacturer/Supplier: Kimball Midwest
 4800 Roberts Road
 Columbus, OH 43228
 800-233-1294
 www.kimballmidwest.com
 ChemTrec: 800-424-9300
 Emergency telephone number:

2 Hazard(s) identification

Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.
 Eye irritation 2A H319 Causes serious eye irritation.
 Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.
 Specific target organ toxicity (single exposure) 3 H336 May cause drowsiness or dizziness.
 Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:
GHS Hazard pictograms

GHS02 GHS07 GHS08

Signal word

Hazard statements

Danger
 Extremely flammable aerosol. Pressurized container: may burst if heated.
 Causes serious eye irritation.
 Suspected of causing cancer. Route of exposure: Inhalation.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Avoid breathing fume/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 IF exposed or concerned, get medical advice.
 If eye irritation persists: Get medical advice/attention.
 Store in a well ventilated place. Keep container tightly closed.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
 Dispose of contents/container in accordance with local/regional/national/international regulations.

Precautionary statements

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	25-50%
74-98-6	propane	15-25%
106-97-8	n-butane	5-10%
110-19-0	Isobutyl Acetate	5-10%
13463-67-7	titanium dioxide	1-5%
108-10-1	methyl isobutyl ketone	1-5%
107-87-9	Methyl Propyl Ketone	1-5%
2807-30-9	Glycol Ether EP	1-5%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
 After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
 After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 2)

Safety Data Sheet

Date of issue: 07/17/2025

Revised On 03/12/2025

Trade name: DOVE GRAY

(Contd. of page 1)

After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects: Dizziness

Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures.

Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up: Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling: Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm

REL (USA) Long-term value: 590 mg/m³, 250 ppm

TLV (USA) Short-term value: 1187 mg/m³, 500 ppm

Long-term value: 594 mg/m³, 250 ppm

A4, BEI

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

(EX)

110-19-0 Isobutyl Acetate

PEL (USA) Long-term value: 700 mg/m³, 150 ppm

REL (USA) Long-term value: 700 mg/m³, 150 ppm

TLV (USA) Short-term value: 712 mg/m³, 150 ppm

Long-term value: 238 mg/m³, 50 ppm

108-10-1 methyl isobutyl ketone

PEL (USA) Long-term value: 410 mg/m³, 100 ppm

REL (USA) Short-term value: 300 mg/m³, 75 ppm

Long-term value: 205 mg/m³, 50 ppm

TLV (USA) Short-term value: 307 mg/m³, 75 ppm

Long-term value: 82 mg/m³, 20 ppm

BEI, A3

107-87-9 Methyl Propyl Ketone

PEL (USA) Long-term value: 700 mg/m³, 200 ppm

REL (USA) Long-term value: 530 mg/m³, 150 ppm

TLV (USA) Short-term value: 529 mg/m³, 150 ppm

Ingredients with biological limit values:**67-64-1 Acetone**

BEI (USA) 25 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

108-10-1 methyl isobutyl ketone

BEI (USA) 1 mg/L

Medium: urine

Time: end of shift

Parameter: MIBK

(Contd. on page 3)

Safety Data Sheet

Date of issue: 07/17/2025

Revised On 03/12/2025

Trade name: DOVE GRAY

(Contd. of page 2)

Hygienic protection:	Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
Hand protection:	Nitrile gloves. The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles

9 Physical and chemical properties

Physical state	Aerosol
Odor:	Aromatic
Odor threshold:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44.5 °C (-48.1 °F)
Flammability:	Extremely flammable.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
pH-value:	Not determined.
Viscosity:	Not determined.
Solubility:	Not determined.
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Particle characteristics	Not applicable.
Appearance:	Aerosol.
Ignition temperature:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Water:	0.0 %
Evaporation rate	Not applicable.
Partition coefficient: n-octanol/water:	Not determined.

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

110-19-0 Isobutyl Acetate

Oral LD50 4,763 mg/kg (rabbit)

13463-67-7 titanium dioxide

Oral LD50 >20,000 mg/kg (rat)
 Dermal LD50 >10,000 mg/kg (rabbit)
 Inhalative LC50/4 h >6.82 mg/l (rat)

108-10-1 methyl isobutyl ketone

Oral LD50 2,100 mg/kg (rat)
 Dermal LD50 16,000 mg/kg (rab)
 Inhalative LC50/4 h 11 mg/l (ATE)
 8.3-16.6 mg/l (rat)

Information on toxicological effects:	No data available.
Skin effects:	No irritant effect.
Eye effects:	Irritating effect.
Sensitization:	No sensitizing effects known.

12 Ecological information

Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.

(Contd. on page 4)

Safety Data Sheet

Date of issue: 07/17/2025

Revised On 03/12/2025

Trade name: DOVE GRAY

Other information:

(Contd. of page 3)
This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.

Bioaccumulative potential:

No further relevant information available.

Mobility in soil:

No further relevant information available.

Other adverse effects:

No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation:

Completely empty cans should be recycled.

Recommended cleansing agent:

Water, if necessary with cleansing agents.

14 Transport information

UN-Number

UN1950

DOT

UN1950

DOT

Aerosols, flammable

ADR

1950 AEROSOLS

Transport hazard class(es):**Class**

2.1 Gases

Special marking (IATA):**Packaging Group:**

--

Special precautions for user:

Warning: Gases

EMS Number:

F-D,S-U

UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-10-1 methyl isobutyl ketone

Toxic Substances Control Act**(TSCA):**

All ingredients are found on the inventory list of substances.

Canadian Domestic Substances List**(DSL):**

All ingredients are listed or exempted.

Consumer Product Safety**Commission (CPSC):**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

108-10-1 methyl isobutyl ketone

100-41-4 ethyl benzene

1333-86-4 Carbon black

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

EPA:

67-64-1 Acetone

110-19-0 Isobutyl Acetate

108-10-1 methyl isobutyl ketone

I

D

I

16 Other information

Contact:

Regulatory Affairs