Date of issue: 08/07/2025 Revised On 08/07/2025

1 Identification of the substance and manufacturer

Trade name: **NEW EQUIPMENT YELLOW**

Other means of identification

Product code: 80-1152

Article category Recommended use:

Paint and coatings application.

Any that differs from the recommended use. Uses advised against:

Kimball Midwest Manufacturer/Supplier: 4800 Roberts Road Columbus, OH 43228

800-233-1294

www.kimballmidwest.com **Emergency telephone number:** ChemTrec: 800-424-9300

2 Hazard(s) identification

Classification of the substance or mixture

Flammable liquids 3 H226 Flammable liquid and vapor. Eye irritation 2A H319 Causes serious eye irritation.

H351 Suspected of causing cancer. Route of exposure: Inhalation. Carcinogenicity 2

Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms**



GHS02 GHS07 GHS08

Warning Signal word

Hazard statements Flammable liquid and vapor. Causes serious eye irritation.

Suspected of causing cancer. Route of exposure: Inhalation.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground / bond container and receiving equipment.

Use explosion-proof [electrical/ventilating/lighting] equipment.

Use non-sparking tools.

Take action to prevent static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous	Dangerous components:		
64742-47-8	Mineral Spirits	15-25%	
7727-43-7	barium sulfate	15-25%	
13463-67-7	titanium dioxide	1-5%	
108-65-6	PM acetate	1-5%	
	xylene (mix)	1-5%	
64742-48-9	Naphtha, hydrotreated heavy	1-5%	

4 First-aid measures

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Rinse mouth with water. Do not induce vomiting Most important symptoms and

effects: No further relevant information available.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Date of issue: 08/07/2025 Revised On 08/07/2025

Trade name: NEW EQUIPMENT YELLOW

Indication of any immediate medical

No further relevant information available.

5 Fire-fighting measures

attention needed:

Special hazards: No further relevant information available. Protective equipment for

firefighters: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for containment and cleaning up: Not required.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store lockéd up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

7727-43-7 barium sulfate

Long-term value: 15* 5** mg/m³ *total dust **respirable fraction PEL (USA)

Long-term value: 10* 5** mg/m³

REL (USA) *total dust **respirable fraction

Long-term value: 5* mg/m3

TLV (USA) *inhalable fraction; E

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm REL (USA)

Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm

TLV (USA) Long-term value: 20 ppm

BEI, A4

111-76-2 Glycol Ether EB

Long-term value: 240 mg/m³, 50 ppm PEL (USA)

REL (USA) Long-term value: 24 mg/m³, 5 ppm

Skin

Long-term value: 97 mg/m³, 20 ppm TLV (USA)

BEI, A3

Ingredients with biological limit values:

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

111-76-2 Glycol Ether EB

BEI (USA) 200 mg/g creatinine

Medium: urine

Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

Hygienic protection: Wash hands after use.

Do not eat or drink while working.

Breathing equipment: Not required.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Physical state Liquid

Odor:

Not determined. Odor threshold: Melting point/Melting range Undetermined.

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Date of issue: 08/07/2025 Revised On 08/07/2025

Trade name: NEW EQUIPMENT YELLOW

Boiling point: Flammability: 175 °C (347 °F) Flammable.

Lower Explosion Limit: 0.5 Vol % 6.5 Vol % 40 °C (104 °F) Upper Explosion Limit: Flash point: Flammability (solid, gas): Flammable. **Decomposition temperature:** Not determined.

pH-value: Viscosity: Not determined. Not determined. Solubility: Not determined. Vapor pressure: Not determined.

Relative Density:

Vapor density Not determined. Particle characteristics Not applicable. Appearance:

Liquid.

Product is not self-igniting. Ignition temperature:

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Water: 0.0 %

Evaporation rate Not determined. Partition coefficient: n-octonal/water: Not determined.

10 Stability and reactivity

Reactivity:

Conditions to avoid: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

ED/LC50 values that are relevant for classification:			
13463-67-7 titanium dioxide			
Oral	LD50	>20,000 mg/kg (rat)	
Dermal	LD50	>10,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>6.82 mg/l (rat)	

108-65-6 PM acetate 8 500 ma/kg (rat) LD50

1330-20-7	xvlene (m	nix)
Inhalative	LC50/4 h	35.7 mg/l (rat)
Orai	LDJU	0,500 mg/kg (rat)

8,700 mg/kg (rat) LD50 Oral

64742-48-9 Naphtha, hydrotreated heavy					
	Inhalative	LC50/4 h	6,350 mg/l (rat)		
	Dermai		2,000 mg/kg (rabbit)		

111-76-2 Glycol Ethor ER					
Dermal	LD50	>3,000 mg/kg (rab)			
Oral	LD50	>5,000 mg/kg (rat)			

LD50 1,200 mg/kg (ATE)

Informatio	No doto		
Inhalative	LC50/4 h	3 mg/l (ATE)	
Dermal		400 mg/kg (rab)	
		1,480 mg/kg (rat)	

No data available. ntormation on toxicological effects: Skin effects: No irritant effect. Eve effects: No irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity:

Hazardous for water, do not empty into drains.
The product is degradable after prolonged exposure to natural weathering processes. Persistence and degradability:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents. Other information:

Bioaccumulative potential: No further relevant information available. No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects:

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

(Contd. on page 4)

Safety Data Sheet

Date of issue: 08/07/2025 Revised On 08/07/2025

Trade name: NEW EQUIPMENT YELLOW

Water, if necessary with cleansing agents. Recommended cleansing agent:

(Contd. of page 3)

14 Transport information

UN-Number

DOT UN1263 DOT

ADR 1263 PAINT (vapour pressure at 50°C not more than 110 kPa)

Transport hazard class(es): Class

Special marking (IATA):

3 Flammable liquids

F-E,<u>S-E</u>

Packaging Group: Special precautions for user: Warning: Flammable liquids

EMS Number:

Stowage Category

UN "Model Regulation": UN 1263 PAINT (VAPOUR PRESSURE AT 50°C NOT MORE THAN 110 KPA), 3, II

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate 1330-20-7 xylene (mix)

Toxic Substances Control Act

(TSCA): All ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide 100-41-4 ethyl benzene 1333-86-4 Carbon black

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

7727-43-7 barium sulfate D, CBD(inh), NL(oral) 1330-20-7 xylene (mix)

16 Other information

Contact: Regulatory Affairs