

# The following SDS references the products below: <u>DURA-INK® 20 RETRACTABLE BULLET TIP Black</u>

Vendor Item Number: N/A

Manufactured By:

LA-CO Industries Inc

Distributed by Kimball Midwest with the KM productidentification number:

83-779 and 83-786

### LA-CO Industries, Inc.

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD) Issue date: 8/3/2020 Revision date: 8/15/2022 Supersedes: 2/17/2021 Version: 2.1

### **SECTION 1: Identification**

1.1.	Identification		
Product form :		: Mixture	
Trade name :		: Dura-Ink® Needle Nose Black	
1.2.	Recommended use and restriction	is on use	
Use of t	he substance/mixture	: Marking.	
Restrict	ions on use	: Any use not specified	
1.3.	Supplier		
LA-CO	Industries, Inc.		
1201 Pratt Boulevard			
Elk Gro			
Phone: (847) 956-7600			
Fax: (84	Fax: (847) 956-9885		
E-mail:	E-mail: customer_service@laco.com		
1.4.	Emergency telephone number		
Emerge	ncy number	: 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887;	
-		<b>全国</b> 应急中心 0532 8388 9090	

### SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

#### **GHS** classification

Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 1 Skin sensitisation, category 1B Germ cell mutagenicity, Category 2 Specific target organ toxicity — Single exposure, Category 3, Narcosis

Hazardous to the aquatic environment — Chronic Hazard, Category 2

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

#### **GHS** labelling

Hazard pictograms (GHS)

H226 Flammable liquid and vapour.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H411 Toxic to aquatic life with long lasting effects.

H315 Causes skin irritation.

Signal word (GHS)	: Danger
Hazard statements (GHS)	<ul> <li>H226 - Flammable liquid and vapour.</li> <li>H315 - Causes skin irritation.</li> <li>H317 - May cause an allergic skin reaction.</li> <li>H318 - Causes serious eye damage.</li> <li>H336 - May cause drowsiness or dizziness.</li> <li>H341 - Suspected of causing genetic defects.</li> <li>H411 - Toxic to aquatic life with long lasting effects.</li> </ul>
Precautionary statements (GHS)	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Ne smoking.</li> <li>P233 - Keep container tightly closed.</li> <li>P240 - Ground/bond container and receiving equipment</li> <li>P241 - Use explosion-proof electrical/ventilating/lighting equipment.</li> <li>P242 - Use only non-sparking tools.</li> <li>P243 - Take precautionary measures against static discharge.</li> <li>P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.</li> <li>P264 - Wash hands, forearms and face thoroughly after handling.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> </ul>
8/15/2022	EN (English) Page

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

	P272 - Contaminated work clothing must not be allowed out of the workplace. P273 - Avoid release to the environment.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352 - If on skin: Wash with plenty of water.
	P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse
	skin with water/shower.
	P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P308+P313 - If exposed or concerned: Get medical advice/attention.
	P310 - Immediately call a poison center or doctor.
	P312 - Call a poison center/doctor if you feel unwell
	P321 - Specific treatment (see supplemental first aid instruction on this label).
	P332+P313 - If skin irritation occurs: Get medical advice/attention.
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
	P362+P364 - Take off contaminated clothing and wash it before reuse.
	P363 - Wash contaminated clothing before reuse.
	P370+P378 - In case of fire: Use media other than water to extinguish.
	P391 - Collect spillage.
	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
	P403+P235 - Store in a well-ventilated place. Keep cool.
	P405 - Store locked up.
	P501 - Dispose of contents/container to hazardous or special waste collection point, in
	accordance with local, regional, national and/or international regulation.
h do not result in a	classification

## 2.3. Other hazards which do not result in classification

No data available

### 2.4. Unknown acute toxicity (GHS)

Not applicable

### **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	% (w/w)	GHS classification
1-Methoxy-2-propanol	(CAS-No.) 107-98-2	25 – 50	Flam. Liq. 3, H226 STOT SE 3, H336
propan-1-ol	(CAS-No.) 71-23-8	25 – 50	Flam. Liq. 2, H225 Eye Dam. 1, H318 STOT SE 3, H336
4,4'-bis(dimethylamino)-4"-(methylamino)trityl alcohol	(CAS-No.) 561-41-1	2.5 – 10	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319 Aquatic Chronic 3, H412
4-(phenylazo)benzene-1,3-diamine; C.I. Solvent Orange 3	(CAS-No.) 495-54-5	2.5 – 10	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Muta. 2, H341 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.	(CAS-No.) 85536-14-7	2.5 - <5	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Aquatic Chronic 3, H412
α,α-bis[4-(dimethylamino)phenyl]-4- (phenylamino)naphthalene-1-methanol; C.I. Solvent Blue 4 (< 0,1% Michler's Ketone)	(CAS-No.) 6786-83-0	≤1	Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

### **SECTION 4: First-aid measures**

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

produits dangereux (RPD)	
First-aid measures after skin contact	: Take off contaminated clothing and wash it before reuse. Wash skin thoroughly with mild soap and water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	<ul> <li>Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.</li> </ul>
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.
4.2. Most important symptoms and	effects (acute and delayed)
Symptoms/effects	: Suspected of causing genetic defects.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness. Inhalation of vapours may cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye damage.
4.3. Immediate medical attention an	nd special treatment, if necessary
Treat symptomatically.	
SECTION 5: Fire-fighting measur	es
5.1. Suitable (and unsuitable) exting	guishing media
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Specific hazards arising from the	ne chemical
Fire hazard	: Flammable liquid and vapour. Flammable vapours may accumulate in the container. Heavier than air, vapours may travel long distances along ground, ignite and flash back to source.
Explosion hazard	: May form flammable/explosive vapour-air mixture. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Reactivity	: No dangerous reactions known.
5.3. Special protective equipment a	nd precautions for fire-fighters
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.
SECTION 6: Accidental release n	neasures
6.1. Personal precautions, protectiv	e equipment and emergency procedures
General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Do not breathe aerosol. Do not breathe vapour. Do not get in eyes, on skin, or on clothing.
6.1.1. For non-emergency personnel	
Protective equipment	: Refer to section 8.2.
Emergency procedures	: Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	: Refer to section 8.2.
Emergency procedures	: Ventilate area.
6.2. Environmental precautions	
Prevent entry to sewers and public waters.	Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.
6.3. Methods and material for conta	inment and cleaning up
For containment	<ul> <li>Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.</li> </ul>
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.
6.4. Reference to other sections	

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# SECTION 7: Handling and storage 7.1. Precautions for safe handling Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Precautions for safe handling	:	Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Do not breathe aerosol. Use only outdoors or in a well-ventilated area. Do not breathe vapours. Do not get in eyes, on skin, or on clothing.
Hygiene measures	:	Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product.
7.2. Conditions for safe storage, includin	ng a	any incompatibilities
Technical measures	:	Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.
Storage conditions	:	Keep in fireproof place. Keep container tightly closed.
Incompatible products	:	Strong oxidizers.
Heat and ignition sources	:	Keep away from heat, sparks and flame.
Storage area	:	Store in dry, cool, well-ventilated area.

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

1-Methoxy-2-propanol (107-98-2)					
ACGIH	Local name	1-Methoxy-2-propanol			
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	369 mg/m <sup>3</sup>			
ACGIH	ACGIH OEL TWA [ppm]	50 ppm			
ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	553 mg/m³			
ACGIH	ACGIH OEL STEL [ppm]	100 ppm			
ACGIH	Remark (ACGIH)	Eye irr; CNS impair; A4 (Not classifiable as a Human Carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of a lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories)			
NIOSH	NIOSH REL TWA	360 mg/m <sup>3</sup>			
NIOSH	NIOSH REL TWA [ppm]	100 ppm			
NIOSH	NIOSH REL STEL	540 mg/m <sup>3</sup>			
NIOSH	NIOSH REL STEL [ppm]	150 ppm			
propan-1-ol (71-23	-8)				
ACGIH	Local name	n-Propanol (n-Propyl alcohol)			
ACGIH	ACGIH OEL TWA [ppm]	100 ppm			
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)			
ACGIH	Regulatory reference	ACGIH 2021			
OSHA	OSHA PEL TWA [1]	500 mg/m <sup>3</sup>			
OSHA	OSHA PEL TWA [2]	200 ppm			
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1			
NIOSH	NIOSH REL TWA	500 mg/m <sup>3</sup>			
NIOSH	NIOSH REL TWA [ppm]	200 ppm			
NIOSH	NIOSH REL STEL	625 mg/m <sup>3</sup>			
NIOSH	NIOSH REL STEL [ppm]	250 ppm			
Benzenesulfonic a Not applicable	cid, 4-C10-13-sec-alkyl derivs. (85536-14-7)				
α,α-bis[4-(dimethylamino)phenyl]-4-(phenylamino)naphthalene-1-methanol; C.I. Solvent Blue 4 (< 0,1% Michler's Ketone) (6786-83-0)					
Not applicable	Not applicable				

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

_			
	4,4'-bis(dimethylamino)-4"-(methylamino)trityl alcohol (561-41-1)		
	Not applicable		
	4-(phenylazo)benzene-1,3-diamine; C.I. Solvent Orange 3 (495-54-5)		
	Not applicable		

#### 8.2. Appropriate engineering controls

Appropriate engineering controls

: Avoid splashing. Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### Hand protection:

Wear suitable gloves. nitrile rubber gloves

#### Eye protection:

Chemical goggles or safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### **Respiratory protection:**

In case of inadequate ventilation wear respiratory protection. Approved respirator

#### Other information:

Do not eat, drink or smoke during use.

#### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solid marker containing liquid colored paint.
Colour	: Black
Odour	: Solvent
Odour threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 96.5 – 97.5 °C
Flash point	: 23 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 19 hPa @ 20 °C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.91 g/cm³ @ 20 °C
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 6.374 mm²/s
Viscosity, dynamic	: 5.8 mPa⋅s @ 20 °C
Explosive limits	: Lower explosive limit (LEL): 1.5 vol % Upper explosive limit (UEL): 13.7 vol %

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

### Explosive properties Oxidising properties

: No data available : No data available

### 9.2. Other information

No data available

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong oxidizers.

### 10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. May release flammable gases.

#### **SECTION 11: Toxicological information** 11.1. Information on toxicological effects Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified 1-Methoxy-2-propanol (107-98-2) LD50 oral rat 4016 mg/kg bodyweight LD50 dermal rat > 2000 mg/kg bodyweight LC50 Inhalation - Rat [ppm] > 7000 ppm 6 hr propan-1-ol (71-23-8) LD50 oral rat 5400 mg/kg LD50 dermal rabbit 4032 mg/kg LC50 Inhalation - Rat > 33.8 mg/l/4h ATE (oral) 5400 mg/kg bodyweight ATE (dermal) 4032 mg/kg bodyweight Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (85536-14-7) LD50 oral rat 1350 mg/kg LD50 dermal rat > 2000 mg/kg ATE (oral) 1350 mg/kg bodyweight α,α-bis[4-(dimethylamino)phenyl]-4-(phenylamino)naphthalene-1-methanol; C.I. Solvent Blue 4 (< 0,1% Michler's Ketone) (6786-83-0) LD50 oral rat > 2000 mg/kg female LD50 dermal rat > 2000 mg/kg 4,4'-bis(dimethylamino)-4"-(methylamino)trityl alcohol (561-41-1) LD50 oral rat > 300 (≤ 2000) mg/kg LD50 dermal rat > 2000 mg/kg ATE (oral) 2000 mg/kg bodyweight 4-(phenylazo)benzene-1,3-diamine; C.I. Solvent Orange 3 (495-54-5) ATE (oral) 500 mg/kg bodyweight Skin corrosion/irritation : Causes skin irritation. Serious eye damage/irritation : Causes serious eye damage. Respiratory or skin sensitisation : May cause an allergic skin reaction.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
1-Methoxy-2-propanol (107-98-2)	
STOT-single exposure	May cause drowsiness or dizziness.
propan-1-ol (71-23-8)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: 6.374 mm²/s
Likely routes of exposure	: Inhalation. Skin and eye contact.
Symptoms/effects	: Suspected of causing genetic defects.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness. Inhalation of vapours may cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye damage.
Other information	: No data available.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

1-Methoxy-2-propanol (107-98-2)			
LC50 fish 1	20800 mg/l		
EC50 crustacea	23300 mg/l		
ErC50 algae	> 1000 mg/l		
propan-1-ol (71-23-8)	propan-1-ol (71-23-8)		
LC50 fish 1	4555 mg/l 96 h		
EC50 crustacea	1000 mg/l 48 h		
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (85536-14-7)			
LC50 fish 1	1.67 mg/l 96 h Lepomis macrochirus		
LC50 other aquatic organisms 1	7.6 mg/l 48 h Hyalella azteca		
NOEC chronic crustacea	≥ 0.5 mg/l 7 d Ceriodaphnia sp.		
α,α-bis[4-(dimethylamino)phenyl]-4-(phenylar	α,α-bis[4-(dimethylamino)phenyl]-4-(phenylamino)naphthalene-1-methanol; C.I. Solvent Blue 4 (< 0,1% Michler's Ketone) (6786-83-0)		
LC50 fish 1	31.64283 mg/l 48 h; Oryzias latipes		
EC50 crustacea	0.025 mg/l 48 h Daphnie		
LC50 - Fish [2]	36.71547 mg/l 96 h; Oncorhynchus mykiss		
NOEC (chronic)	0.4063749 mg/l 504 h; daphnia magna		
4,4'-bis(dimethylamino)-4''-(methylamino)trityl alcohol (561-41-1)			
LC50 fish 1	1.6 mg/l 96 h Zebra fish		
EC50 crustacea	10.8 mg/l 48 h		
NOEC chronic fish	0.293 mg/l 28 d		

### 12.2. Persistence and degradability

Dura-Ink® Needle Nose Black	
Persistence and degradability	May cause long-term adverse effects in the environment.
1-Methoxy-2-propanol (107-98-2)	
Persistence and degradability	Readily biodegradable.
Biodegradation	96 % 28 d
propan-1-ol (71-23-8)	
Persistence and degradability	Readily biodegradable.
Biodegradation	75 % 20 d

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)


roduits dangereux (RPD)	
Benzenesulfonic acid, 4-C10-13-sec-alkyl	derivs. (85536-14-7)
Persistence and degradability	Readily biodegradable.
Biodegradation	94 % 28 d
α,α-bis[4-(dimethylamino)phenyl]-4-(pher	ylamino)naphthalene-1-methanol; C.I. Solvent Blue 4 (< 0,1% Michler's Ketone) (6786-83-0)
Persistence and degradability	Not readily biodegradable.
Biodegradation	50 % estimated
4,4'-bis(dimethylamino)-4"-(methylamino)	trityl alcohol (561-41-1)
Persistence and degradability	Not readily biodegradable.
12.3. Bioaccumulative potential	
Dura-Ink® Needle Nose Black	
Bioaccumulative potential	Not established.
1-Methoxy-2-propanol (107-98-2)	
Bioaccumulative potential	Not expected to bioaccumulate.
propan-1-ol (71-23-8)	
BCF fish 1	0.88
Log Pow	0.2
-	Nulamina)nanhthalana 1 mathanali C.I. Salvant Plua 4 ( -0.49) Miaklaria ((atana) (6700.02.0)
α,α-bis[4-(dimethylamino)phenyi]-4-(pher Bioconcentration factor (BCF REACH)	nylamino)naphthalene-1-methanol; C.I. Solvent Blue 4 (< 0,1% Michler's Ketone) (6786-83-0) 10000 estimated
Log Pow	0.8055
Bioaccumulative potential	Expected to bioaccumulate.
•	
4,4'-bis(dimethylamino)-4"-(methylamino)	4,365
Log Pow	4.303
12.4. Mobility in soil	
Dura-Ink® Needle Nose Black	
Ecology - soil	Not established.
12.5. Other adverse effects	
Other information	: Avoid release to the environment.
SECTION 13: Disposal considerati	ons
13.1. Disposal methods	
Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.
SECTION 14: Transport informatio	in the second
SECTION 14. Transport mormatio	11
14.1. UN number	
DOT NA No	: UN3082
UN-No. (TDG)	: 3082
UN-No. (IMDG)	: 3082
UN-No. (IATA)	: 3082
14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-(phenylazo)benzene-1,3-
	diamine; C.I. Solvent Orange 3)
Proper Shipping Name (TDG)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-(phenylazo)benzene-1,3-
	diamine; C.I. Solvent Orange 3)
Proper Shipping Name (IMDG)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-(phenylazo)benzene-1,3-
Proper Shipping Name (IATA)	<ul><li>diamine; C.I. Solvent Orange 3)</li><li>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-(phenylazo)benzene-1,3-</li></ul>

(IATA) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-(phenylazo)benzene-1,3diamine; C.I. Solvent Orange 3)

### 14.3. Transport hazard class(es)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)



Other information

# 8/15/2022

Preliminary Screening Test.

: Per ICAO/IATA Regulations 3.4.1.1.2; IMDG Regulations 2.4.2.2.2 Product testing according to the UN regulations for classification of readily combustible solids section 33.2.1.4.3.1 –

Inner filter with absorbed ink is removed from marker body. End of filter is ignited using 2000°C

Marine Pollutants /Environmentally Hazardous Substances exempt from Regulations when packaging contains a net quantity per single or inner packaging is of 5 kgs / 5 liters or less. References : ICAO Special Provision A197, IMDG 2.10.2.7, 49 CFR 171.4(C)(1)(2).

torch. After 2 minutes rate of burning is less than 2 mm per second.

Product is not readily combustible solid of Division 4.1.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

SECTION 15: Regulatory information	
15.1. US Federal regulations	
All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory	
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (85536-14-7)	
EPA TSCA Regulatory Flag PMN - PMN - indicates a commenced PMN substance.	
45.0 Internetional resultations	
15.2. International regulations CANADA	
1-Methoxy-2-propanol (107-98-2) Listed on the Canadian DSL (Domestic Substances List) inventory.	
propan-1-ol (71-23-8) Listed on the Canadian DSL (Domestic Substances List) inventory.	
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (85536-14-7) Listed on the Canadian DSL (Domestic Substances List) inventory.	
	0.00.0
α,α-bis[4-(dimethylamino)phenyl]-4-(phenylamino)naphthalene-1-methanol; C.I. Solvent Blue 4 (< 0,1% Michler's Ketone) (678) Listed on the Canadian DSL (Domestic Substances List) inventory.	J-83-0)
4,4'-bis(dimethylamino)-4"-(methylamino)trityl alcohol (561-41-1) Listed on the Canadian DSL (Domestic Substances List) inventory.	
4-(phenylazo)benzene-1,3-diamine; C.I. Solvent Orange 3 (495-54-5) Listed on the Canadian DSL (Domestic Substances List) inventory.	
Listed on the Canadian DSE (Domestic Substances List) inventory.	
National regulations	
Dura-Ink® Needle Nose Black	
All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).	
1-Methoxy-2-propanol (107-98-2)	
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on NZIOC (New Zealand Inventory of Chemicals) Listed on Taiwan National Chemical Inventory Listed on the AICS (Australian Inventory of Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on KECL/KECI (Korean Existing Chemicals Inventory)	
propan-1-ol (71-23-8)	
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Chinese Catalog of Hazardous Chemicals. Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on Taiwan National Chemical Inventory Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the AICS (Australian Inventory of Chemical Substances) Listed on KECL/KECI (Korean Existing Chemicals Inventory)	
α,α-bis[4-(dimethylamino)phenyl]-4-(phenylamino)naphthalene-1-methanol; C.I. Solvent Blue 4 (< 0,1% Michler's Ketone) (678	6-83-0)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on NZIOC (New Zealand Inventory of Chemicals) Listed on Taiwan National Chemical Inventory Listed on the AICS (Australian Inventory of Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on KECL/KECI (Korean Existing Chemicals Inventory)	
4-(phenylazo)benzene-1,3-diamine; C.I. Solvent Orange 3 (495-54-5)	
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on NZIOC (New Zealand Inventory of Chemicals) Listed on Taiwan National Chemical Inventory Listed on the AICS (Australian Inventory of Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory	

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm.

Component	State or local regulations
1-Methoxy-2-propanol(107-98-2)	U.S Idaho - Occupational Exposure Limits - Ceilings; U.S Idaho - Non- Carcinogenic Toxic Air Pollutants - Emission Levels (ELs); U.S Idaho - Non- Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S Minnesota - Hazardous Substance List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York - Right to Know List of Hazardous Chemicals; U.S Washington - Permissible Exposure Limits - STELs; U.S Washington - Permissible Exposure Limits - TWAs
propan-1-ol(71-23-8)	U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

### **SECTION 16: Other information**

Revision date	: 02/17/2021
Data sources	: ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html.
Other information	: None.
Full text of H-statements:	

Full	text of H-statements:	
	11005	

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Abbreviations and acronyms:

ACGIH (American Conference of Government Industrial Hygienists)
CAS (Chemical Abstracts Service) number
CLP: Classification, Labelling, Packaging.
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
OSHA: Occupational Safety & Health Administration
PBT: Persistent, Bioaccumulative, Toxic
TSCA: Toxic Substances Control Act

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.
Indication of changes: Transport information.	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.