

1. Product And Company Identification

GHS product identifier: Dielectric Grease - Pressure Can

Other means of identification: 80-967

Relevant identified uses of the substance or mixture and uses advised against:

Silicone Compound

Supplier's details: Kimball Midwest

4800 Roberts Road Columbus, OH 43228

Corporate Telephone: 800.233.1294

CHEMTREC, 24 hours/day, 7 days/week

Emergency telephone number:

U.S.: 1-800-424-9300

International: +1-703-527-3887

SDS Date of Preparation: 08/08/2018

2. Hazards Identification

GHS Classification:

Physical:	Health:
Gases Under Pressure: Compressed Gas	Reproductive Toxicity Category 2

GHS Label Elements:





Warning!

Statements of Hazard	Precautionary phrases
Contains gas under pressure; may explode if heated.	Protect from sunlight. Store in a well-ventilated place.
Suspected of damaging fertility or the unborn child.	Obtain special instructions before use.
	Do not handle until all safety precautions have been
	read and understood.
	IF exposed or concerned: Get medical attention.
	Store locked up.
	Dispose of contents and container in accordance with
	local and national regulations.

3. Composition/Information on Ingredients

Component	CAS No.	Amount
1,1-Difluoroethane	75-37-6	<1%
Trimethoxyboroxin	102-24-9	<0.5%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First Aid Measures

Inhalation: If symptoms of exposure develop, remove to fresh air. Seek medical attention if breathing problem or irritation persists.

Skin Contact: Wash exposed skin with soap and water for several minutes. If skin irritation develops, seek medical attention.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice or attention.

Ingestion: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Most Important Symptoms: May cause mild eye of respiratory irritation. Suspected of damaging fertility or the unborn child.

Indication of Immediate Medical Attention/Special Treatment: None known.

5. Firefighting Measures

Suitable (and Unsuitable) Extinguishing Media: Use dry chemical, foam, carbon dioxide, or water spray.

Specific Hazards Arising from the Chemical: Not classified as flammable but contains a flammable propellant. Contents under pressure. Burning may produce carbon oxides, formaldehyde, and silicon dioxide. Exposure of containers to heat and flames can cause them to rupture often with violent force.

Special Fire Fighting Procedures: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures: Ventilate the area. Wear appropriate protective clothing and equipment.

Methods and Materials for Containment and Clean-Up: Place leaking can in a pail in a well-ventilated area until pressure has dissipated. Collect residual liquid using inert absorbents and place into a suitable container for disposal.

Environmental Precautions: Report release as required by local and national regulations.

7. Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes and skin. Avoid breathing gas. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Contents under pressure, do not puncture or incinerate containers.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, dry, well-ventilated area, away from strong oxidizers and other incompatible materials. Do not store in direct sunlight or above 120°F. U.F.C. (NFPA 30B) Level 1 Aerosol.

8. Exposure Controls / Personal Protection

Exposure Guidelines:

CHEMICAL	EXPOSURE LIMIT
1,1-Difluoroethane	1000 ppm TWA AIHA WEELs
Trimethoxyboroxin	None Established

Appropriate Engineering Controls: General ventilation should be adequate for normal use. For operations where the exposure limits may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable limits.

Personal Protective Equipment

Respiratory Protection: None under normal use conditions. For operations where the exposure limits may be exceeded, a NIOSH approved supplied air respirators recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134; all applicable laws and regulations; and good industrial hygiene practice.

Gloves: Impervious gloves recommended to avoid skin contact.

Eye Protection: Safety glasses are recommended if eye contact is possible.

Other Protective Equipment/Clothing: None required.

9. Physical and Chemical Properties

Appearance and Odor: Translucent paste with a slight sweet odor.

Physical State: Thick liquid under pressure	Odor Threshold: Not determined	
pH: Not determined	Specific Gravity: 1.03 (Liquid component)	
Initial Boiling Point/Range: > 300 °C (> 572 °F)	Vapor Pressure: Not determined	
(Liquid component)		
Melting/Freezing Point: Not determined	Vapor Density: (Air = 1) >1 (Liquid component)	
Solubility In Water: Insoluble	Percent Volatile: Not determined	
Viscosity: Not determined	Evaporation Rate: (n-butyl acetate = 1.0):	
	Not determined	
Decomposition Temperature: Not available	VOC Content: 10 g/L (Liquid component)	
Coefficient Of Water/Oil Distribution: Not determined	Autoignition Temp: Not determined	
Flash Point: > 300 °C (> 572 °F) (Liquid component)	Flame extension: Not determined	
Flammability Limits: LEL: 3.7% (1,1-Difluoroethane)	Flammability (solid, gas): Not applicable	
UEL: 18% (1,1-Difluoroethane)		

10. Stability and Reactivity

Reactivity: Not normally reactive

Chemical Stability: Stable under normal storage and handling conditions

Possibility of Hazardous Reactions: None expected.

Conditions to Avoid: Keep away from excessive heat, and open flames. Containers may rupture at temperatures

> 120°F (48.8°C).

Incompatible Materials: Strong oxidizing agents, strong bases, and strong acids.

Hazardous Decomposition Products: May produce carbon oxides, formaldehyde, and silicon dioxide.

11. Toxicological Information

Potential Health Effects:

Acute Hazards:

Inhalation: Vapors can irritate the throat and respiratory tract.

Skin Contact: May cause mild irritation.

Eye Contact: May cause mild irritation.

Ingestion: Swallowing may cause gastrointestinal disturbances.

Chronic Effects: Contains Trimethoxyboroxin. Boron compounds are suspected of damaging fertility or the

unborn child.

Carcinogenicity Listing: None of the components listed is a carcinogen or potential carcinogen by IARC, NTP,

ACGIH or OSHA

Numerical Measures of Toxicity:

Product ATE: LD50 Oral > 5,000 mg/kg

LD50 Dermal >2,000 mg/kg

1,1-Difluoroethane: LC50 Inhalation Rat: 437,500ppm/4h

Trimethoxyboroxin: LD50 Oral Rat: 4,080 mg/kg

LD50 Dermal Rabbit: >2,000 mg/kg

12. Ecological Information

Ecotoxicity:

1,1-Difluoroethane: LC50 Fish 719.61 mg/L/ 96hr (Calculated)

Persistence and Degradability: No data available for product.

Bio accumulative Potential: No data available for product.

Mobility in Soil: No data available for product.

Other Adverse Effects: No data available

13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

14. Transport Information

DOT Hazardous Materials Description: UN1950, Aerosols, 2.2 LTD QTY

IMDG Dangerous Goods Description: UN1950, Aerosols 2.2 LTD QTY

15. Regulatory Information

United States:

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CERCLA Section 103: This product has no RQ, however, oil spills must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Classified under OSHA Hazcom 2012 GHS as per Section 2 of this SDS.

SARA 313: This product contains the following chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372): None

California Proposition 65: Warning not required.

16. Other Information

REVISION DATE: 08/08/2018

REVISION SUMMARY: New SDS

DATE OF PREVIOUS REVISION: N/A

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.