



SAFETY DATA SHEET

Issuing date 01-Mar-2019

Revision Date 19-Sep-2023

Version 1.03

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name Acry-Maxx Multi-Purpose
Solvent

Other means of identification

Product code

80-1557

Product Type

Synonyms Extremely Flammable
Aerosol None

Recommended use of the chemical and restrictions on use

Recommended Use MULTI-PURPOSE SOLVENT.

Uses advised against No information available

Manufactured For:

Kimball Midwest
4800 Roberts Rd.
Columbus, OH 43228
800-233-1294

Emergency telephone number

Chemical Emergency Phone Number CHEMTREC : 1-800-424-9300

Company Emergency Phone Number 1-800-233-1294

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration hazard	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

Label elements

Emergency Overview

Danger

Hazard statements

Causes skin irritation

Causes serious eye irritation

Suspected of causing cancer

May cause respiratory irritation. May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

May cause damage to organs (Eyes, Skin, Respiratory System, Central Nervous System, and Hearing) through prolonged or repeated exposure.

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance Clear

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves, eye protection, face protection.

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice, attention.

Specific treatment (see first aid on this label).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice, attention.

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice, attention.
Take off contaminated clothing and wash it before reuse.
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER or doctor, physician if you feel unwell.
IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.
Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

Not applicable

Other information

Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

0 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
PETROLEUM DISTILLATES	64742-89-8	60-70
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
XYLENE	1330-20-7	1-10
ETHYL BENZENE	100-41-4	1-10

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures**

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, consult a doctor.
Skin contact	Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.
Protection of First-aiders	Remove all sources of ignition.

Most important symptoms and effects, both acute and delayed

Main Symptoms Causes skin and serious eye irritation. Suspected of causing cancer. May cause respiratory

irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog.Dry chemical. Foam.Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition. In the event of fire and/or explosion do not breathe fumes.

Hazardous Combustion Products Acrid smoke/fumes. Carbon oxides , Hydrocarbons, Fumes. Sulfur oxides.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers. In the event of fire and/or explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Report spills as required by local and federal regulations. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

Methods and material for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inter, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly . After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Contents under pressure. Do not

puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety practice. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products

Strong acids, alkalis, oxidizing agents.

Aerosol Level

3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6: TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8: TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5: TWA: 800 ppm TWA: 1900 mg/m ³
XYLENE 1330-20-7	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	Not Established
ETHYL BENZENE 100-41-4	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
TOLUENE 108-88-3	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
BENZENE 71-43-2	STEL: 2.5 ppm TWA: 0.5 ppm S*	TWA: 10 ppm applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028 TWA: 1 ppm (vacated) TWA: 10 ppm unless specified in 1910.1028 (vacated) STEL: 50 ppm 10 min unless specified in 1910.1028 (vacated) Ceiling: 25 ppm unless specified in 1910.1028 Ceiling: 25 ppm STEL: 5 ppm see 29 CFR 1910.1028	IDLH: 500 ppm TWA: 0.1 ppm STEL: 1 ppm
NAPHTHALENE 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
CUMENE 98-82-8	TWA: 5 ppm	TWA: 50 ppm TWA: 245 mg/m ³	IDLH: 900 ppm TWA: 50 ppm

		(vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S* S*	TWA: 245 mg/m ³
--	--	---	----------------------------

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Ventilation systems. Use adequate ventilation to keep the exposure levels below the occupational exposure limits. Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tightly fitting safety goggles.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Aerosol		
Appearance	Clear	Odor	Solvent
Color	Clear	Odor Threshold	
Property	Values	Remarks • Method	
pH	No information available	No information available	
Melting/freezing point	No information available		
Boiling point/boiling range	No information available		
Flash Point	-97 °C / -143 °F	Based on propellant	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
upper flammability limit			
lower flammability limit	No information available		
Vapor pressure			
Vapor density	No information available		
Specific gravity	0.955		
Water solubility	Insoluble in water		
Partition coefficient: n-octanol/water			
Autoignition temperature	No information available	Not applicable	
Hyphen			
Viscosity	No information available		
Explosive properties			

Other information

VOC Content(%) 100

10. STABILITY AND REACTIVITY

Reactivity

Stable under recommended storage conditions No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible materials

Strong acids, alkalis, oxidizing agents.

Hazardous decomposition products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Inhalation	May cause respiratory irritation, May cause drowsiness or dizziness.
Eye contact	Causes serious eye irritation.
Skin contact	Causes skin irritation.
Ingestion	May be fatal if swallowed and enters airways.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
PETROLEUM DISTILLATES 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Causes skin and serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause respiratory irritation. May cause damage to organs (listed below) through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.
Eye damage/irritation Irritating to eyes.
Sensitization Not a known sensitizer.
Germ cell mutagenicity Not a germ cell mutagen.
Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
XYLENE 1330-20-7	-	Group 3	-	-
ETHYL BENZENE 100-41-4	A3	Group 2B	-	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

This product does not contain any known or suspected reproductive hazards.

Specific target organ systemic toxicity (single exposure)

May cause respiratory irritation. May cause drowsiness or dizziness.

Specific target organ systemic toxicity (repeated exposure)

None known. May cause damage to Target Organs listed below through prolonged or repeated exposure.

Chronic toxicity

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.

Target organ effects

Eyes, Skin, Respiratory System, Central Nervous System, and Hearing.

Neurological effects

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Aspiration hazard

May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information**Unknown acute toxicity**

0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document**ATEmix (oral)**

61141 mg/kg

ATEmix (dermal)

14121 mg/kg

ATEmix (inhalation-gas)

96971 ppm mg/l

ATEmix (inhalation-dust/mist)

18.5 mg/l

ATEmix (inhalation-vapor)

1037.5 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Very toxic to aquatic life with long lasting effects

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
PETROLEUM DISTILLATES 64742-89-8	EC50: =4700mg/L (72h, Pseudokirchneriella subcapitata)	-	-	-
PROPANE/ISOBUTANE/N- BUTANE 68476-86-8	-	-	-	-
XYLENE 1330-20-7	-	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio)	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)

		LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata)		
ETHYL BENZENE 100-41-4	EC50: ≈4.6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >438mg/L (96h, Pseudokirchneriella subcapitata) EC50: 2.6 - 11.3mg/L (72h, Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 11.0 - 18.0mg/L (96h, Oncorhynchus mykiss) LC50: ≈4.2mg/L (96h, Oncorhynchus mykiss) LC50: 7.55 - 11mg/L (96h, Pimephales promelas) LC50: ≈32mg/L (96h, Lepomis macrochirus) LC50: 9.1 - 15.6mg/L (96h, Pimephales promelas) LC50: ≈9.6mg/L (96h, Poecilia reticulata)	-	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)

Persistence and degradability**Bioaccumulation**

Chemical name	Partition coefficient
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8
XYLENE 1330-20-7	3.15
ETHYL BENZENE 100-41-4	3.6

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment****Waste Disposal Methods**

Dispose of in accordance with federal, state, and local regulations. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations. Dispose of in accordance with local regulations.

Contaminated packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION**DOT Ground**

LIMITED QUANTITY

IATA

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD .QTY.

IMDG

UN1950, AEROSOLS, 2.1, LTD.QTY

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PETROLEUM DISTILLATES	X	X	X	Not listed	X	X	X	X
PROPANE/ISOBUTA NE/N-BUTANE	X	X	X	x	X	X	X	X
XYLENE	X	X	X	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
XYLENE - 1330-20-7	1330-20-7	1-10	1.0
ETHYL BENZENE - 100-41-4	100-41-4	1-10	0.1
TOLUENE - 108-88-3	108-88-3	<0.1	1.0
BENZENE - 71-43-2	71-43-2	<0.1	0.1
NAPHTHALENE - 91-20-3	91-20-3	<0.1	0.1
CUMENE - 98-82-8	98-82-8	<0.1	0.1

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
---------------	--------------------------	---------------------------------------	--------------------------

XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical name	California Proposition 65
ETHYL BENZENE - 100-41-4	Cancer/ 1-10%
TOLUENE - 108-88-3	Developmental / <0.1%
BENZENE - 71-43-2	Cancer Developmental (Male)/ <0.1%
NAPHTHALENE - 91-20-3	Cancer / <0.1%
CUMENE - 98-82-8	Cancer / <0.1%

Note

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
PETROLEUM DISTILLATES 64742-89-8			X
XYLENE 1330-20-7	X	X	X
ETHYL BENZENE 100-41-4	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA	Health hazards 2	Flammability 4 2	Instability 0	Special hazards -
HMIS	Health hazards 2*	Flammability 4 2	Physical hazards 1	Personal protection B
Chronic Hazard Star Legend * = Chronic Health Hazard				

Prepared By Regulatory Affairs
 Issuing date 01-Mar-2019
 Revision Date 19-Sep-2023
 Revision Note
 (M)SDS sections updated 1 3 8 11 12 15
Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet