

# S-S-T Stainless Steel Towels

## Safety Data Sheet

### SECTION 1: Product and company identification

Product name : S-S-T Stainless Steel Towels  
Use of the substance/mixture : Premoistened wipe  
Product code : 80-565  
Company : KIMBALL MIDWEST  
4800 Roberts Rd  
COLUMBUS, OH 43228  
T 800-233-1294  
Emergency number : Chemtrec 800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

GHS-US classification  
Flam. Liq. 4 H227  
Skin Sens. 1 H317  
Asp. Tox. 1 H304

#### 2.2. Label elements

GHS US labelling

Hazard pictograms (GHS US)



GHS07

GHS08

Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: Combustible liquid

May be fatal if swallowed and enters airways.

May cause an allergic skin reaction.

Precautionary statements (GHS US)

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Avoid breathing dust, fume.

Contaminated work clothing must not be allowed out of the workplace.

Wear eye protection, protective gloves.

If swallowed: Immediately call a POISON CENTER.

If on skin: Wash with plenty of water.

Do NOT induce vomiting.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use Water spray, extinguishing powder, foam to extinguish.

Store locked up.

Dispose of contents/container to comply with local/regional/national/international regulations.

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Hydrotreated Light Alkanes (Solvent)	(CAS-No.) 64742-47-8	45 – 60	Flam. Liq. 4, H227 Asp. Tox. 1, H304
Mineral Oil (Solvent)	(CAS-No.) 8042-47-5	15 – 40	Asp. Tox. 1, H304
d-Limonene (Solvent)	(CAS-No.) 5989-27-5	1 – 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304

# S-S-T Stainless Steel Towels

## Safety Data Sheet

All hazardous chemicals, as determined by 29 CFR 1910.1200 have been listed. A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- |                                       |  |
|---------------------------------------|--|
| First-aid measures general            | : Call a physician immediately.  |
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing.   |
| First-aid measures after skin contact | : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact  | : Rinse eyes with water as a precaution.   |
| First-aid measures after ingestion    | : Do not induce vomiting. Call a physician immediately.  |

#### 4.2. Most important symptoms and effects, both acute and delayed

- |                                     |   |
|-------------------------------------|---|
| Symptoms/effects after inhalation   | : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. |
| Symptoms/effects after skin contact | : May cause an allergic skin reaction.  |
| Symptoms/effects after eye contact  | : None under normal conditions.   |
| Symptoms/effects after ingestion    | : Risk of lung oedema.  |

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- |                                |  |
|--------------------------------|--|
| Suitable extinguishing media   | : Water spray. Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.               |

#### 5.2. Special hazards arising from the substance or mixture

- |                  |   |
|------------------|---|
| Fire hazard      | : Combustible liquid.                                 |
| Explosion hazard | : No direct explosion hazard.                         |
| Reactivity       | : Upon combustion: CO and CO <sub>2</sub> are formed. |

#### 5.3. Advice for firefighters

- |                                |   |
|--------------------------------|---|
| Firefighting instructions      | : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.              |

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- |                  |   |
|------------------|---|
| General measures | : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage. |
|------------------|---|

##### 6.1.1. For non-emergency personnel

- |                      |   |
|----------------------|---|
| Protective equipment | : Wear recommended personal protective equipment.   |
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. |

##### 6.1.2. For emergency responders

- |                      |   |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : Evacuate unnecessary personnel. Stop leak if safe to do so.   |

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- |                         |   |
|-------------------------|---|
| For containment         | : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible. |
| Methods for cleaning up | : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.   |
| Other information       | : Dispose of materials or solid residues at an authorized site.   |

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

# S-S-T Stainless Steel Towels

## Safety Data Sheet

### 7.1. Precautions for safe handling

- |                                   |   |
|-----------------------------------|---|
| Additional hazards when processed | : Not expected to present a significant hazard under anticipated conditions of normal use.  |
| Precautions for safe handling     | : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. |
| Hygiene measures                  | : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.   |

### 7.2. Conditions for safe storage, including any incompatibilities

- |                              |   |
|------------------------------|---|
| Technical measures           | : Keep in a cool, well-ventilated place away from heat.                     |
| Storage conditions           | : Store in a well-ventilated place. Keep cool. Store locked up.             |
| Information on mixed storage | : KEEP SUBSTANCE AWAY FROM: oxidizing agents.                               |
| Packaging materials          | : Store always product in container of same material as original container. |

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### d-Limonene (5989-27-5)

Not applicable

#### Mineral Oil (8042-47-5)

ACGIH	ACGIH OEL TWA	5 mg/m <sup>3</sup> (Inhalable fraction)
-------	---------------	--

#### Hydrotreated Light Alkanes (64742-47-8)

Not applicable

### 8.2. Exposure controls

- |                                  |   |
|----------------------------------|---|
| Appropriate engineering controls | : Ensure good ventilation of the work station.  |
| Personal protective equipment    | : Safety glasses. Gloves. Use appropriate personal protective equipment when risk assessment indicates this is necessary. |



- |                                 |   |
|---------------------------------|---|
| Hand protection                 | : Protective gloves.  |
| Eye protection                  | : Safety glasses.   |
| Skin and body protection        | : Wear suitable protective clothing.  |
| Respiratory protection          | : In case of insufficient ventilation, wear suitable respiratory equipment. |
| Environmental exposure controls | : Avoid release to the environment.   |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- |   |  |
|---|--|
| Physical state                                  | : Solid  |
| Appearance                                      | : Premoistened wipe  |
| Odour   | : Citrus scent   |
| Odour threshold                                 | : No data available  |
| pH  | : No data available  |
| Melting point                                   | : Not applicable   |
| Freezing point                                  | : No data available  |
| Boiling point                                   | : No data available  |
| Flash point                                     | : 197 °F Closed cup - Tested using the liquid component of the towelette |
| Relative evaporation rate (butylacetate=1)      | : No data available  |
| Flammability                                    | : No data available  |
| Explosive limits                                | : No data available  |
| Explosive properties                            | : No data available  |
| Oxidising properties                            | : No data available  |
| Vapour pressure                                 | : No data available  |
| Relative density                                | : No data available  |
| Relative vapour density at 20°C                 | : No data available  |
| Density   | : 0.81 g/ml Tested using the liquid component of the towelette           |
| Solubility                                      | : Liquid component is not soluble in water.                              |
| Partition coefficient n-octanol/water (Log Pow) | : No data available  |
| Partition coefficient n-octanol/water (Log Kow) | : No data available  |
| Auto-ignition temperature                       | : No data available  |
| Decomposition temperature                       | : No data available  |
| Viscosity                                       | : No data available  |

# S-S-T Stainless Steel Towels

## Safety Data Sheet

Viscosity, kinematic	: < 20 cSt - Tested using the liquid component of the towelette
Viscosity, dynamic	: No data available
VOC content	: < 3 % Tested using the liquid component of the towelette

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Upon combustion: CO and CO<sub>2</sub> are formed.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

##### d-Limonene (5989-27-5)

LD50 oral rat	> 2000 mg/kg bodyweight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Read-across, Dermal, 7 day(s))

##### Mineral Oil (8042-47-5)

LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 5 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Read-across, Inhalation (aerosol), 14 day(s))

##### Hydrotreated Light Alkanes (64742-47-8)

LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

##### d-Limonene (5989-27-5)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

##### Hydrotreated Light Alkanes (64742-47-8)

# S-S-T Stainless Steel Towels

## Safety Data Sheet

NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Risk of lung oedema.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
-------------------	---

d-Limonene (5989-27-5)	
LC50 - Fish [1]	720 µg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 - Crustacea [1]	0.307 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, GLP)
LC50 - Fish [2]	702 µg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [2]	0.51 mg/l Test organisms (species): Daphnia magna

Mineral Oil (8042-47-5)	
LC50 - Fish [1]	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)

Hydrotreated Light Alkanes (64742-47-8)	
LC50 - Fish [1]	2.4 mg/l Source: ECOTOX

### 12.2. Persistence and degradability

d-Limonene (5989-27-5)	
Persistence and degradability	Readily biodegradable in water.
ThOD	3.29 g O <sub>2</sub> /g substance

Mineral Oil (8042-47-5)	
Persistence and degradability	Not readily biodegradable in water.

### 12.3. Bioaccumulative potential

d-Limonene (5989-27-5)	
BCF - Fish [1]	864.8 l/kg (BCFBAF v3.01, Pisces, QSAR, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	4.38 (Experimental value, Equivalent or similar to OECD 117, 37 °C)
Bioaccumulative potential	Potential for bioaccumulation (4 ≤ Log Kow ≤ 5).

Mineral Oil (8042-47-5)	
BCF - Other aquatic organisms [1]	1216 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	5.2 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

Hydrotreated Light Alkanes (64742-47-8)	
Partition coefficient n-octanol/water (Log Pow)	3.3 – 6 Source: IUCLID

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.

# S-S-T Stainless Steel Towels

## Safety Data Sheet

Additional information : Do not re-use empty containers.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

#### Additional information

Other information : This product is classified as a combustible liquid and is exempt from the U.S. DOT's Hazardous Materials Regulations when shipped in non-bulk packages. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may be required.

#### ADR

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations


All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

### SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.  
NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.  
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.