Safety Data Sheet

Date of issue: 08/07/2025 Revised On 03/12/2025

1 Identification of the substance and manufacturer

White Athletic Field Water-Based Marking Paint Trade name:

Other means of identification

80915 Product code:

Article category Recommended use:

Paint and coatings application. Uses advised against:

Any that differs from the recommended use. Kimball Manufacturer/Supplier:

Midwest

4800 Roberts Road Columbus, OH 43228 800-233-1294

www.kimballmidwest.com Emergency telephone number: ChemTrec: 800-424-9300

2 Hazard(s) identification

Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

Eye irritation 2A H319 Causes serious eye irritation.

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

H336 Specific target organ toxicity (single exposure) 3 May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: GHS Hazard pictograms

Precautionary statements







GHS02 GHS07 GHS08

Signal word

Hazard statements Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes serious eye irritation.

Suspected of causing cancer. Route of exposure: Inhalation.

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. IF exposed or concerned, get medical advice

If eye irritation persists: Get medical advice/attention. Store in a well ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:				
	Acetone	15-25% 15-25%		
	-6 propane			
	Calcium Carbonate 10-15%			
	3 n-butane 5-10%			
	-1 methyl isobutyl ketone			
	PM acetate	5-10%		
	xylene (mix)	1-5%		
	Glycol Ether EP	1-5%		
123-86-4	butyl acetate	1-5%		

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

Date of issue: 08/07/2025 Revised On 03/12/2025

(Contd. of page 1)

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical

attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.

Protective equipment for

firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

6 Exposure controls/personal protection				
Components with limit values that require monitoring at the workplace:				
67-64-1 Acetone				
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm			
REL (USA)	Long-term value: 590 mg/m³, 250 ppm			
TLV (USA)	Short-term value: 1187 mg/m³, 500 ppm			
` ′	Long-term value: 594 mg/m³, 250 ppm			
	A4, BEI			
74-98-6 propane				
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm			
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm			
TLV (USA)	see Appendix F Minimal oxygen content (D, EX)			
106-97-8 n-butane				
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm			
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm			
` ,	(EX)			
108-10-1 methyl isobutyl ketone				
PEL (USA)	Long-term value: 410 mg/m³, 100 ppm			

PEL (USA)	Long-term value: 410 mg/m³, 100 ppm
REL (USA)	Short-term value: 300 mg/m³, 75 ppm Long-term value: 205 mg/m³, 50 ppm
	Long-term value: 205 mg/m³, 50 ppm
TLV (USA)	Short-term value: 307 mg/m³, 75 ppm Long-term value: 82 mg/m³, 20 ppm BEI. A3

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

1330-20-7 xylene (mix)

PEL (USA)	Long-term value: 435 mg/m³, 100 ppm
REL (USA)	Short-term value: 655 mg/m³, 150 ppm
,	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV (USA)	Long-term value: 20 ppm

BEI, A4 123-86-4 butyl acetate

PEL (USA)	Long-term value: 710 mg/m³, 150 ppm
REL (USA)	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
	Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 3)

(Contd. of page 2)

Date of issue: 08/07/2025 Revised On 03/12/2025

108-10-1 methyl isobutyl ketone

BEI (USA) 1 mg/L Medium: urine

Time: end of shift Parameter: MIBK

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine Medium: urine

Time: end of shift Parameter: Methylhippuric acids

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In **Breathing equipment:**

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Physical state Aerosol Odor: Aromatic Odor threshold: Not determined. Melting point/Melting range Undetermined. Boiling point: Flammability: -44 °C (-47.2 °F) Extremely flammable.

Lower Explosion Limit: 1.7 Vol % Upper Explosion Limit: 10.9 Vol % -19 °C (-2.2 °F) Flash point: Flammability (solid, gas): Extremely flammable. Decomposition temperature: Not determined. pH-value: Not determined. . Viscositv: Not determined. Solubility: Not determined. Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. Particle characteristics Not applicable. Aerosol.

Appearance:

Ignition temperature: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Water: 0.0 %

Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

8,700 mg/kg (rat)

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD50

Oral

LD/LC50 values that are relevant for classification:							
108-10-1 r	108-10-1 methyl isobutyl ketone						
Oral	LD50	2,100 mg/kg (rat)					
Dermal	LD50	16,000 mg/kg (rab)					
Inhalative	LC50/4 h	11 mg/l (ATE)					
		8.3-16.6 mg/l (rat)					
108-65-6 F	108-65-6 PM acetate						
Oral	LD50	8,500 mg/kg (rat)					
Inhalative	Inhalative LC50/4 h 35.7 mg/l (rat)						
1330-20-7	1330-20-7 xylene (mix)						

(Contd. on page 4)

ı

1

ı

Safety Data Sheet

Date of issue: 08/07/2025 Revised On 03/12/2025

Dermal LD50 2,000 mg/kg (rabbit) (Contd. of page 3)

Inhalative LC50/4 h 6,350 mg/l (rat)

123-86-4 butyl acetate

14,000 mg/kg (rat) Oral LD50 Inhalative LC50/4 h >21 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eve effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Persistence and degradability: Hazardous for water, do not empty into drains.

The product is degradable after prolonged exposure to natural weathering processes.

Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's),

perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl

substances (PFA's), or chlorinated solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be

disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 DOT UN1950

DOT Aerosols, flammable **ADR** 1950 AEROSOLS

Transport hazard class(es): Class 2.1 Gases

Special marking (IATA):

Packaging Group:

Special precautions for user: Warning: Gases

EMS Number: F-D,S-U

UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed

SARA Section 313 (Specific toxic chemical listings):

108-10-1 methyl isobutyl ketone

1330-20-7 xylene (mix)

Toxic Substances Control Act

All ingredients are found on the inventory list of substances. (TSCA):

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

108-10-1 methyl isobutyl ketone

100-41-4 ethyl benzene

13463-67-7 titanium dioxide

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

EPA:

67-64-1 Acetone 108-10-1 methyl isobutyl ketone

1330-20-7 xylene (mix)

16 Other information

Contact: Regulatory Affairs

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.